

Treating Blue Pearl

Blue Pearl is a hard stone that belongs to the group of syenites. The crystals embedded into this unique material reflect light and produce a sparkling look. This optical effect is best seen on polished materials. As with every other natural stone, adequate treatment and care are essential to maintaining the stone's appearance for many years.

General Notes



Please note that some varieties of this material react sensitively around the edges of the crystals. These sensitive edges are attacked by acidic substances, such as vinegar, lemon juice, ketchup, wine, acidic cleaners, etc. Avoid contact with such substances on polished or honed surfaces.

Before Grouting

Apply the impregnator intended for the finishing treatment prior to grouting. This pre-treatment acts as a grout release and greatly facilitates removing cement and mortar residues.

△ Please note that cement residue removers are acid based. They are therefore not suitable for polished and honed surfaces. Thoroughly washing the surface with water directly after grouting is therefore essential.

Initial Cleaning



Scrub or wipe the surface with Lithofin MN Power-Clean diluted 1:10 to receive a clear and clean surface.



Light cement residues from the grouting material on polished and honed surfaces: Apply Lithofin MN Power-Clean diluted 1:3 and allow the solution to work for approx. 10 minutes. Carefully remove the residues with a white nylon pad and without applying pressure.

Other Types of Dirt

oil, grease, care product residues	Lithofin MN Power-Clean
tar, wax, sealants	Lithofin WAX-OFF
oil stains	Lithofin OIL-EX
calcium deposits	Lithofin MN Power-Clean and a white nylon pad

Protective Treatment

Areas sensitive to staining like floors, tables, kitchen work tops, etc. should be treated with a protective impregnator. This treatment will render the surface water and oil repellent. The treatment prevents staining and makes maintenance cleaning easier.

The solvent based impregnator protects all natural stone surfaces and does not change the appearance. Lithofin STAINSTOP >W<* is the water based alternative and ideally suited for surfaces in inhabited buildings where the smell of organic solvents is unwanted.

△ **Please note:** all impregnators can only be applied to completely dried out surfaces. We highly recommend testing the product in a small area or on a cut-off. The application is simple: apply with a mop or a wide brush and allow the treatment to sink into the surface. Before (approx. 15 minutes), excess product by towelling. Impregnators do not protect acidic substances. the treatment after approx. 3 years is recommended.



drying
remove all
off.
against
Refreshing



Regular Maintenance



For normal use, it is sufficient to wipe the pavement regularly with a damp cloth. Add Lithofin MN Wash & Clean to the wiper fluid – this way you can clean and care for it in one go. Highly grease-dissolving agents and leaching soft soaps are not suitable for

long-term care.

To refresh and maintain polished surfaces, we recommend adding Lithofin MN Care-Sheen to the water occasionally (about every 4th time instead of MN Wash & Clean).

If you require advice or are in any way unsure about these instructions, please call our **Technical Support Line at 0044 (0)1962 732 126**



△ This information can and should only provide non-binding advice. The use of a product must be adapted to the local conditions and the surfaces to be treated. The suitability of the product shall be determined on a test area.

*For industrial and professional use only.

GB.66 / Ref. 41010 Edition D1.21gps

Your LITHOFIN-Dealer:

The Professional Solution

Distribution in UK and Ireland:

Lithofin MN Stain-Stop* is the ideal protective treatment.
EAGLEON Enterprises Ltd. Alesford, Hampshire SO24 9QF · Phone: +44 1962 732 126 · sales@lithofin.co.
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk