

Cleaning - Protecting - Maintaining Dolomite marble -kitchen worktops-

Instructions for polished, sanded and brushed surfaces

Dolomite marble has little or only limited resistance to acids due to calcitic impurities. Acidic substances (vinegar, lemon, wine, descaling agents, etc.) as well as strong alkalis can lead to acid burns. Choosing the right treatment guarantees the long life of your natural stone kitchen counter.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin MN Power-Clean -acid free- removes greasy and general dirt




Coverage:
1Litre/10m²



Distribute a squirt of Lithofin MN Power-Clean on the wet surface and scrub.



Rinse well with water to remove all product residues.



Allow to dry. Do not wet the surface for 24 hours.

Tip: Existing surfaces should also be cleaned from time to time with Lithofin MN Power-Clean.

Necessary equipment: sponge


2

Protecting against stains *initial cleaning of used surfaces: Page 2*


Lithofin FVE with colour enhancing effect renders the surface water and oil repellent



Coverage:
1Litre/15m²



Please note.




Pour product in a basin or bucket.



Apply with a brush. Also treat the edges and front edge of the underside.



Distribute or remove excess product, streaks and puddles within 15 minutes.



Allow to dry. Do not walk on surface for approx. 45 minutes and protect from water for 24 hours.

Necessary equipment: basin or bucket, roller, brush, cloth

3

Regular maintenance *additional maintenance tips: Page 2*

Lithofin MN Easy-Clean -used regularly- cleans and provides additional protection.



500ml



Spray the surface then wipe with a moist cloth.

Follow-up treatment

To maintain the optimum protective effect, treat once a year with Lithofin STAINSTOP >W<. For flamed and brushed surfaces, clean occasionally with Lithofin MN Power-Clean.



Apply a thin layer of Lithofin STAINSTOP >W< and spread until dry.

Necessary equipment: cleaning cloth, polishing cloth

All recommended products are safe for health after drying. If the cleaning products are used properly, no harmful substances will remain on the stone surface.

Please follow the detailed instructions on the product label.

GB6.26 / Ref. 42004 Edition D1.24sz

1 Cleaning and refurbishing used surfaces

Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.

- Lithofin MN Power-Clean is suitable for all types of stone. Dilute up to 1:3 with water and apply with a brush or sponge.
- Allow to work for 5 to 10 minutes. Scrub well and wait another 5 minutes.
- Add water while scrubbing and remove the solution from the surface.
- Rinse twice with clear water to remove all product residues.

Other, stubborn types of dirt

oil, grease, etc.	Lithofin MN Power-Clean
tar, wax, varnish, paint	Lithofin WAX-OFF
deeply engrained oil stains	Lithofin OIL-EX
calcium deposits	Lithofin MN Power-Clean, undiluted with 10 min. exposure time and rub with a white pad

2 Additional information about protective treatments

Impregnation with Lithofin FVE renders the surface water and oil resistant. The treatments' protective effect reduces staining and facilitates every-day maintenance. Treating the surface improves the appearance by invigorating the colour structure. Protective treatments enhance the appearance and make natural stone less sensitive. In general, an existing sensitivity to acids is not changed by impregnation.

Lithofin STAINSTOP >W< can also be applied to surfaces that have already been impregnated with Lithofin FVE (e.g. in the factory) and is therefore particularly suitable for subsequent treatment. We recommend re-treatment with Lithofin STAINSTOP >W< once a year to maintain optimum protection. Not suitable for polished surfaces. The active ingredients pose no health concerns after drying.

Please Note:

- **Always test the product in an inconspicuous area.** Non-absorbent or wet surfaces cannot be treated.
- Use impregnators only on completely dry surfaces. Otherwise, the product will not be able to penetrate into the surface.
- Apply the product evenly. Do not allow streaks or puddles to dry, as this is no longer possible after drying. If the product is already beginning to dry, moisten the cloth with product if necessary.

Please Note:

- △ Please follow the detailed instructions on the label.
- △ Dolomite marble has little or only limited resistance to acids due to calcitic impurities. Acidic substances (vinegar, lemon, wine, descaling agents, etc.) as well as strong alkalis can lead to chemical burns.

TIP: Avoid using leaching and degreasing cleaning products as well as products that form layers.

These products negatively affect the appearance of the natural stone and make maintenance more difficult.

This information should be considered to be informal and non-binding.
The products must be used according to local conditions and materials.
Instructions must be read carefully and followed closely. Always test the product in an inconspicuous area.

If you require advice or are in any way unsure
about these instructions, please call our
Technical Support Line at 0044 (0)1962 732 126

Your LITHOFIN-Dealer:

The Professional Solution

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 1962 732 126 · sales@lithofin.co.

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk